



FIXED LIGHT  
(SA)

**N|TECH 0.7**



- High performance passive design
- Fantastic energy saving
- Large secure glazed areas
- Custom-made shapes and sizes
- Solid construction
- Great weather performance



Enhanced security



Safe for children



Sound reduction



Energy saving



Optional aluminium cladding



- Aluminium clad corner section, viewed externally

# FIXED LIGHT (SA)



■ *NorDan's fixed light window, interior view*



Custom angled shapes available to suit your design.



*Fixed light exterior view, standard timber*



*Fixed light exterior view, aluminium clad timber*

## CONSTRUCTION

Fixed lights are available glazed or with insulated panels allowing for inclusion of non-vision panels.

### INSULATED FRAME

A layer of insulation is laminated into the 105mm deep frame offering a solid, high performance construction. Timber is double vacuum impregnated for protection and has full PEFC chain of custody accreditation.

### TRIPLE GLAZED SEALED UNIT

Improved energy saving unit contains low emissivity glass and argon filled cavities: 4E5mm + 16mm Argon + 4mm + 16mm Argon + ES4mm. Other glazing options are available. Warm edge technology is employed in the spacer bars to improve the thermal efficiency of the sealed unit.

## OPTIONS

### OPTIONAL ALUMINIUM CLADDING

Aluminium cladding increases the life-span of the window and also greatly reduces maintenance costs. Cladding can be powder coated from any colour in the RAL classic range.

### FURTHER OPTIONS

- Custom-made angled shapes are available to suit your design
- Mullions and transoms
- Multi-sash and combination windows (fixed and opening lights) all in one frame are also available
- Factory pre-finished to any colour from the RAL classic range

### AVAILABLE SIZES

Min width	238 mm
Max width	2988 mm
Min height	238 mm
Max height	2988 mm
Max width + height	5000 mm

NOTE: Size limitations also depend on the weight of the glazing, for further information please contact your nearest NorDan office.